

EASY PAINT PRODUCT SPECIFICATION

WATERBASED EMERALD SERIES - INTERIOR & EXTERIOR



PRODUCT DESCRIPTION :

Easy Paint is acrylic based mixed with modified soft polymer paint for good rub resistance, water resistance, smooth surface, odour less, can be washed, free from powder(chalk), small crack sealer, no primer or undercoat required, easy to apply, anti dirt, can used on metal, wood, cement wall & other surfaces with free from lead and mercury which is specially formula for exterior and interior wall. This premium high class exterior and interior is formula to make easy to use. Performance at least 5 year protection against fungus and algae, chalking and flaking. (term & condition)

RECOMMENDED USES :

For decoration and protection of exterior and interior wall.
Can be used on metal, wood, cement wall and other surfaces.

STANDARD AND INDEPENDENT REPORT :
SIRIM TEST REPORT NO: 2017CE0704

COMPOSITION :

Pigment	: Titanium Dioxide, Mineral Extender, Iron Oxide, Black Carbon & Organic Pigment
Blinder	: Acrylic Base & Acrylic Soft Ploymer
Base adjuster	: Water
Properties	
Colour	: Wide range of colour (custom made colour)
Appearance	: Semi - gloss finish
Recommended coat	: Minimum 2 layer coats
Drying Time	: 40 min Dependent on temperature and humidity.
Recoating	: 1- 2 hour
Theoretical Cover area	: 10 -13 m / square per coat (Coverage is dependent on substrate condition)

SURFACE PREPARATION :

1. Remove all loose , defective paint or powdery residues by wire brush, scraping, or high pressure water jet.
2. Treat any areas affected with anti fungus grown, Repair cracks, allow all surfaces dry prior painting.
3. Avoid painting when the moisture high
*Recommended painting requires the moisture is below 10% and alkalinity below pH9

RECOMMENDED PAINTED SURFACES :

Type of substrate
Masonry

Sealer : with or without (Dependent on necessity)
Creation product without sealer or undercoat

Finish : EMERALD colour minimum 2 layer

Standard packing : 5liter (6+kg) 18liter (22+kg)



APPLICATION GUIDE :

Optional uses :

Apply directly Emerald on wall's surface

Equipment : Brush or Roller
(Either dilute with 2%-5% water)

Air Spray : Dilute with 10%-20% water)

Clean up wash : Quick clean up equipment with thinner after use. Stain difficult to remove after dry.